
















MARCA	IMAGEN	MODELO	DESCRIPCION
P-TECH		CT-50-10-G-R-ADV	CONTROLADOR AUTOCLAVE 50 RECETAS 10 PASOS/RECETA. PANTALLA 7" + PLC 16IN/16OUT + MODULO 4 AI
P-TECH		USB-RS485	CONVERTIDOR DE INTERFAZ RS485-USB
HAIWELL		T32S2T-e	PLC ALIMENTACION 220VAC, 16DI/24VDC, 16DO/NPN, RS232+RS485+ETHERNET, MAX 7 MODULOS
HAIWELL		C7	HMI 7" TFT 800x480, 800MHz CPU, 4GB FLASH + 512MB DDR3, RS232+RS485+SD CARD+ETHERNET+HAIWELL CLOUD (ACCESO REMOTO DESDE CELULAR)
HAIWELL		H08XDT	MODULO DE EXPANSION 24VDC 4DI 4DO NPN
HAIWELL		S04AI	MODULO 4AI 12BITS, 24VDC, RS485
HAIWELL		S04AO	MODULO 4AO 12BITS, 24VDC, RS485
HAIWELL		ACA20	CABLE DE PROGRAMACION RS232
SHQJ		HF41F/24-Z	RELE DE INTERFAZ 24VDC 6A/250VAC SPDT
SHQJ		41F-1Z-C2-1	SOCKET PARA RELE HF41F 12-24VDC
MAXWELL		FT900-P-R-2-96-P42-N-N	CONTROLADOR DE RAMPA 4 PROGRAMAS 32 SEGMENTOS 96x96mm 85-265VAC SALIDA RELE 2 ALARMAS RETRANSMISION 4-20mA

MAXWELL		FT900-P-V-2-96-P42-N-N	CONTROLADOR DE RAMPA 4 PROGRAMAS 32 SEGMENTOS 96x96mm 85-265VAC SALIDA SSR 2 ALARMAS RETRANSMISION 4-20mA
MAXWELL		FT100-612-R-1-1-96-N-N-N	CONTROLADOR + TEMPORIZADOR 48x48 SALIDA RELE
MAXWELL		CH102-FK02-MV*AB	CONT. DE TEMPERATURA 48x48mm SALIDA RELE+SSR 2 ALARMAS
MAXWELL		CH402-FK02-MV*AB	CONT. DE TEMPERATURA 48x96mm SALIDA RELE+SSR 2 ALARMAS
MAXWELL		CH502-FK02-MV*AB	CONT. DE TEMPERATURA 96x48mm SALIDA RELE+SSR 2 ALARMAS
MAXWELL		CH702-FK02-MV*AB	CONT. DE TEMPERATURA 72x72mm SALIDA RELE+SSR 2 ALARMAS
MAXWELL		CH902-FK02-MV*AB	CONT. DE TEMPERATURA 96x96mm SALIDA RELE+SSR 2 ALARMAS
MAXWELL		MTB-48-R-N-1-96-N	CONT. DE TEMPERATURA 48x48mm SALIDA RELE
MAXWELL		MTB-48-V-N-1-96-N	CONT. DE TEMPERATURA 48x48mm SALIDA SSR
MAXWELL		MTB-48-D-N-1-96-N	CONT. DE TEMPERATURA 48x48mm SALIDA 4-20mA
MAXWELL		MTB-49-R-N-1-96-N	CONT. DE TEMPERATURA 48x96mm SALIDA RELE
MAXWELL		MTB-49-V-N-1-96-N	CONT. DE TEMPERATURA 48x96mm SALIDA SSR
MAXWELL		MTB-49-D-N-1-96-N	CONT. DE TEMPERATURA 48x96mm SALIDA 4-20mA
MAXWELL		MTB-94-R-N-1-96-N	CONT. DE TEMPERATURA 96x48mm SALIDA RELE
MAXWELL		MTB-94-V-N-1-96-N	CONT. DE TEMPERATURA 96x48mm SALIDA SSR
MAXWELL		MTB-94-D-N-1-96-N	CONT. DE TEMPERATURA 96x48mm SALIDA 4-20mA
MAXWELL		MTB-72-R-N-1-96-N	CONT. DE TEMPERATURA 72x72mm SALIDA RELE
MAXWELL		MTB-72-V-N-1-96-N	CONT. DE TEMPERATURA 72x72mm SALIDA SSR
MAXWELL		MTB-72-D-N-1-96-N	CONT. DE TEMPERATURA 72x72mm SALIDA 4-20mA
MAXWELL		MTB-96-R-N-1-96-N	CONT. DE TEMPERATURA 96x96mm SALIDA RELE

MAXWELL		MTB-96-V-N-1-96-N	CONT. DE TEMPERATURA 96x96mm SALIDA SSR
MAXWELL		MTB-96-D-N-1-96-N	CONT. DE TEMPERATURA 96x96mm SALIDA 4-20mA
MAXWELL		MS-1-DA-48-10	SSR 1~ ENTRADA 3-32VDC SALIDA 10A/480VAC
MAXWELL		MS-1-DA-48-25	SSR 1~ ENTRADA 3-32VDC SALIDA 25A/480VAC
MAXWELL		MS-1-DA-48-40	SSR 1~ ENTRADA 3-32VDC SALIDA 40A/480VAC
MAXWELL		MS-1-DA-48-60	SSR 1~ ENTRADA 3-32VDC SALIDA 60A/480VAC
MAXWELL		MS-1-DA-48-80	SSR 1~ ENTRADA 3-32VDC SALIDA 80A/480VAC
MAXWELL		MS-1-DA-48-100	SSR 1~ ENTRADA 3-32VDC SALIDA 100A/480VAC
MAXWELL		MS-1-DA-48-120	SSR 1~ ENTRADA 3-32VDC SALIDA 120A/480VAC
MAXWELL			MW-I
MAXWELL		MW-W-A	DISIPADOR PARA SSR MONOFASICO 40A
MAXWELL		MW-W-B	DISIPADOR PARA SSR MONOFASICO 60A
MAXWELL		MW-T	DISIPADOR PARA SSR MONOFASICO 80/100/120A
MAXWELL		MS-3-DA-38-10	SSR 3~ ENTRADA 3-32VDC SALIDA 10A/380VAC
MAXWELL		MS-3-DA-38-25	SSR 3~ ENTRADA 3-32VDC SALIDA 25A/380VAC
MAXWELL		MS-3-DA-38-40	SSR 3~ ENTRADA 3-32VDC SALIDA 40A/380VAC
MAXWELL		MS-3-DA-38-60	SSR 3~ ENTRADA 3-32VDC SALIDA 60A/380VAC
MAXWELL		MS-3-DA-38-80	SSR 3~ ENTRADA 3-32VDC SALIDA 80A/380VAC
MAXWELL		MS-3-DA-38-100	SSR 3~ ENTRADA 3-32VDC SALIDA 100A/380VAC
MAXWELL		MS-3-DA-38-120	SSR 3~ ENTRADA 3-32VDC SALIDA 120A/380VAC
MAXWELL		MS-3-DA-38-150	SSR 3~ ENTRADA 3-32VDC SALIDA 150A/380VAC
MAXWELL		MS-3-DA-38-200	SSR 3~ ENTRADA 3-32VDC SALIDA 200A/380VAC
MAXWELL			MW-L
MAXWELL		MW-H-A	DISIPADOR PARA SSR TRIFASICO 40A
MAXWELL		MW-H-B	DISIPADOR PARA SSR TRIFASICO 60A
MAXWELL		MW-Y-A	DISIPADOR PARA SSR TRIFASICO 80A
MAXWELL		MW-Y-B	DISIPADOR PARA SSR TRIFASICO 100/120A
MAXWELL		MW-Y-C	DISIPADOR PARA SSR TRIFASICO 150/200A









MAXWELL		DS4130-J-S-2-SUS304-5-35-1500-L4-T2-M8-U	TC-J SONDA SUS304 5(ϕ)x35(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-K-S-2-SUS304-5-35-1500-L4-T2-M8-U	TC-K SONDA SUS304 5(ϕ)x35(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-PT100-S-B-SUS304-5-35-1500-L4-T2-M8-3	PT100 SONDA SUS304 5(ϕ)x35(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-J-S-2-SUS304-5-45-1500-L4-T2-M8-U	TC-J SONDA SUS304 5(ϕ)x45(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-K-S-2-SUS304-5-45-1500-L4-T2-M8-U	TC-K SONDA SUS304 5(ϕ)x45(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-PT100-S-B-SUS304-5-45-1500-L4-T2-M8-3	PT100 SONDA SUS304 5(ϕ)x45(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-J-S-2-SUS304-5-50-1500-L4-T2-M8-U	TC-J SONDA SUS304 5(ϕ)x50(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-K-S-2-SUS304-5-50-1500-L4-T2-M8-U	TC-K SONDA SUS304 5(ϕ)x50(L)mm M8 CABLE 1.5m
MAXWELL		DS4130-PT100-S-B-SUS304-5-50-1500-L4-T2-M8-3	PT100 SONDA SUS304 5(ϕ)x50(L)mm M8 CABLE 1.5m
MAXWELL			DS4300-J-S-2-SUS304-5mm-13mm-175mm-2000mm-L6-T2-4.5-BC2/4.5/12-U
MAXWELL	DS4300-K-S-2-SUS304-5mm-13mm-175mm-2000mm-L6-T2-4.5-BC2/4.5/12-U		TC-K BAYONETA SUS304 5(ϕ)x13(L) mm CABLE 2m
MAXWELL		DS4310-J-S-2-SUS304-5mm-4mm-5mm-2000mm-L6-T2-M6-U	TC-J TORNILLO SUS304 5(ϕ)x4(L)mm M6 CABLE 2m
MAXWELL		DS4310-K-S-2-SUS304-5mm-4mm-5mm-2000mm-L6-T2-M6-U	TC-K TORNILLO SUS304 5(ϕ)x4(L)mm M6 CABLE 2m
MAXWELL		DS3200-J-S-2-SUS304-1.5mm-150mm-1000mm-L6-T2-U	TC-J AGUJA SUS304 1.5(ϕ)x150(L)mm CABLE 1m
MAXWELL		DS3200-K-S-2-SUS304-1.5mm-150mm-1000mm-L6-T2-U	TC-K AGUJA SUS304 1.5(ϕ)x150(L)mm CABLE 1m
MAXWELL		DS4540-H1010-PT100-S-B-SUS304-6-100-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(ϕ)x100(L)mm NPT1/2" SIMPLE
MAXWELL		DS4540-H1010-PT100-D-B-SUS304-6-100-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(ϕ)x100(L)mm NPT1/2" DOBLE

MAXWELL		DS4540-H1010-PT100-S-B-SUS304-6-150-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(φ)x150(L)mm NPT1/2" SIMPLE
MAXWELL		DS4540-H1010-PT100-D-B-SUS304-6-150-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(φ)x150(L)mm NPT1/2" DOBLE
MAXWELL		DS4540-H1010-PT100-S-B-SUS304-6-200-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(φ)x200(L)mm NPT1/2" SIMPLE
MAXWELL		DS4540-H1010-PT100-D-B-SUS304-6-200-M20x1.5mm-NPT1/2-3	PT100 CABEZAL SUS304 BULBO 6(φ)x200(L)mm NPT1/2" DOBLE
OMCH		TX-PT100-3x7x0.20	CABLE APANTALLADO PARA PT100 3x7x0.20 FORRO FIBRA DE VIDRIO
P-TECH		D148-WD	TRANSMISOR DE TEMPERATURA
P-TECH		3D-E	MEDIDOR DE POTENCIA TRIFASICO 96x96mm V / A / W / VAR / PF / Hz / Wh / VARh / %RH - TEMP / CORRIENTE RESIDUAL mA
P-TECH		PZEM-061	MEDIDOR MONOFASICO 80-260VAC 0-100A, V / A / W / KW-h, INC. TRANSFORMADOR
P-TECH		ME-AA51	AMPERIMETRO DIGITAL AC
P-TECH		ME-DA51	AMPERIMETRO DIGITAL DC
P-TECH		ME-AV51	VOLTIMETRO DIGITAL AC
P-TECH		ME-DV51	VOLTIMETRO DIGITAL DC
P-TECH		DR-30-24	FUENTE ALIMENTACION 88-264VAC SALIDA 24VDC 1.3A
P-TECH		DR-60-24	FUENTE ALIMENTACION 88-264VAC SALIDA 24VDC 2.5A

NATURAL		860204	VENTILADOR+FILTRO+REJILLA 220VAC 92x92mm IP54 32-41 m3/h CON FILTRO DE SALIDA
NATURAL		860207	VENTILADOR+FILTRO+REJILLA 220VAC 124x124mm IP54 100-120 m3/h CON FILTRO DE SALIDA
NATURAL		860056	RESISTENCIA CALEFACTORA 30W 120-240VAC/VDC
NATURAL		860059	RESISTENCIA CALEFACTORA 60W 120-240VAC/VDC
NATURAL		860006	TERMOSTATO 0-60°C NA IP20
NATURAL		860001	TERMOSTATO 0-60°C NC IP20

NATURAL		860041	TERMOSTATO DUAL 0-60°C NA+NC IP20
P-TECH		CS-PT1000-4B-0.5-1-D-NPT1/4-1	TRANSMISOR DE PRESION CALIB. 0-4BAR 4-20mA NPT1/4"
P-TECH		CS-PT1000-6B-0.5-1-D-NPT1/4-1	TRANSMISOR DE PRESION CALIB. 0-6BAR 4-20mA NPT1/4"
P-TECH		CS-PT1000-10B-0.5-1-D-NPT1/4-1	TRANSMISOR DE PRESION CALIB. 0-10BAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-0.3B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-300mBAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-0.5B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-500mBAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-1B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-1BAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-4B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-4BAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-6B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-6BAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-10B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-10BAR 4-20mA NPT1/4"
P-TECH		CS-PT1200-20B-0.5-1-D-NPT1/4	TRANSMISOR DE PRESION 0-20BAR 4-20mA NPT1/4"
P-TECH		CS-PT510-10mB-V2-0.5	TRANSMISOR DE PRESION DIFERENCIAL 0-10mBAR 0-10VDC
OMCH		BEN5M-MDT	SENSOR FOTOELECTRICO RETROREFLECTIVO Sn=0,1-5m ALIMENTACION 12-24VDC SALIDA NPN/PNP
OMCH		BR400-DDT	SENSOR FOTOELECTRICO DIFUSO METALICO M18 Sn=400mm ALIMENTACION 12-24VDC SALIDA NPN
OMCH		E3F1-DS5C4	SENSOR FOTOELECTRICO DIFUSO PLASTICO M12 Sn=200mm ALIMENTACION 10-30VDC SALIDA NPN-NA
OMCH		BF4R	AMPLIFICADOR DE FIBRA OPTICA 12-24VDC SALIDA NPN NA-NC SENSIBILIDAD AJUSTABLE
OMCH		FD-620-10	CABLE DE FIBRA OPTICA DIFUSO M6 Sn=120mm CURVATURA MAX. R30 LONGITUD 2m
SOMMY		CR-18P8C	SENSOR CAPACITIVO M18 8mm SALIDA PNP-NA
SOMMY		CR-18N8C	SENSOR CAPACITIVO M18 8mm SALIDA NPN-NA
SOMMY		CR-30P15C	SENSOR CAPACITIVO M30 15mm SALIDA PNP-NA
SOMMY		CR-30N15C	SENSOR CAPACITIVO M30 15mm SALIDA NPN-NA
HEYI		LICP18A3-8-Z/BY	SENSOR CAPACITIVO M30 15mm SALIDA PNP-NA



HEYI		LJCP18A3-8-Z/BX	SENSOR CAPACITIVO M18 8mm SALIDA NPN-NA
SOMMY		PR-8P2C	SENSOR INDUCTIVO M8 2mm SALIDA PNP-NA
SOMMY		PR-8N2C	SENSOR INDUCTIVO M8 2mm SALIDA NPN-NA
SOMMY		PR-12P2C	SENSOR INDUCTIVO M12 2mm SALIDA PNP-NA
SOMMY		PR-12N2C	SENSOR INDUCTIVO M12 2mm SALIDA NPN-NA
SOMMY		PR-12P4C	SENSOR INDUCTIVO M12 4mm SALIDA PNP-NA
SOMMY		PR-12N4C	SENSOR INDUCTIVO M12 4mm SALIDA NPN-NA
SOMMY		PR-18P5C	SENSOR INDUCTIVO M18 5mm SALIDA PNP-NA
SOMMY		PR-18N5C	SENSOR INDUCTIVO M18 5mm SALIDA NPN-NA
SOMMY		PR-18P8C	SENSOR INDUCTIVO M18 8mm SALIDA PNP-NA
SOMMY		PR-18N8C	SENSOR INDUCTIVO M18 8mm SALIDA NPN-NA
SOMMY		PR-30P10C	SENSOR INDUCTIVO M30 10mm SALIDA PNP-NA
SOMMY		PR-30N10C	SENSOR INDUCTIVO M30 10mm SALIDA NPN-NA
SOMMY		PR-30P15C	SENSOR INDUCTIVO M30 15mm SALIDA PNP-NA
SOMMY		PR-30N15C	SENSOR INDUCTIVO M30 15mm SALIDA NPN-NA
HEYI		LJ08A3-2-Z/BY	SENSOR INDUCTIVO M8 2mm SALIDA PNP-NA
HEYI		LJ08A3-2-Z/BX	SENSOR INDUCTIVO M8 2mm SALIDA NPN-NA
HEYI		LJ12A3-2-Z/BY	SENSOR INDUCTIVO M12 2mm SALIDA PNP-NA
HEYI		LJ12A3-2-Z/BX	SENSOR INDUCTIVO M12 2mm SALIDA NPN-NA
HEYI		LJ12A3-4-Z/BY	SENSOR INDUCTIVO M12 4mm SALIDA PNP-NA
HEYI		LJ12A3-4-Z/BX	SENSOR INDUCTIVO M12 4mm SALIDA NPN-NA
HEYI		LJ18A3-5-Z/BY	SENSOR INDUCTIVO M18 5mm SALIDA PNP-NA
HEYI		LJ18A3-5-Z/BX	SENSOR INDUCTIVO M18 5mm SALIDA NPN-NA
HEYI		LJ18A3-8-Z/BY	SENSOR INDUCTIVO M18 8mm SALIDA PNP-NA
HEYI		LJ18A3-8-Z/BX	SENSOR INDUCTIVO M18 8mm SALIDA NPN-NA
HEYI		LJ30A3-10-Z/BY	SENSOR INDUCTIVO M30 10mm SALIDA PNP-NA
HEYI		LJ30A3-10-Z/BX	SENSOR INDUCTIVO M30 10mm SALIDA NPN-NA
HEYI		LJ30A3-15-Z/BY	SENSOR INDUCTIVO M30 15mm SALIDA PNP-NA
HEYI		LJ30A3-15-Z/BX	SENSOR INDUCTIVO M30 15mm SALIDA NPN-NA
HEYI		LJ18A3-5-J/EZ	SENSOR INDUCTIVO M18 5mm SALIDA NA 90-250VAC
HEYI		LJ18A3-8-J/EZ	SENSOR INDUCTIVO M18 8mm SALIDA NA 90-250VAC

HEYI		LJ12A3-2-Z/BY-G	SENSOR IND. M12 2mm SALIDA PNP-NA CONECTOR
HEYI		LJ12A3-2-Z/BX-G	SENSOR IND. M12 2mm SALIDA NPN-NA CONECTOR
HEYI		LJ12A3-4-Z/BY-G	SENSOR IND. M12 4mm SALIDA PNP-NA CONECTOR
HEYI		LJ12A3-4-Z/BX-G	SENSOR IND. M12 4mm SALIDA NPN-NA CONECTOR
HEYI		LJ18A3-5-Z/BY-G	SENSOR IND. M18 5mm SALIDA PNP-NA CONECTOR
HEYI		LJ18A3-5-Z/BX-G	SENSOR IND. M18 5mm SALIDA NPN-NA CONECTOR
HEYI		LJ18A3-8-Z/BY-G	SENSOR IND. M18 8mm SALIDA PNP-NA CONECTOR
HEYI		LJ18A3-8-Z/BX-G	SENSOR IND. M18 8mm SALIDA NPN-NA CONECTOR
HEYI		G3-2m	CABLE CONECTOR RECTO M12 2m
HEYI		G1-5m	CABLE CONECTOR RECTO M12 5m
RACING LEAD		LTA-505-3-R/Y/G-AC220V-TJ-FZL3	T. DE LUZ R/A/V+ZUMB. 220VAC CONTINUO 47(φ)x570(H)mm
RACING LEAD		LTA-505-3-R/Y/G-DC24V-TJ-FZL3	T. DE LUZ R/A/V+ZUMB. 24VDC CONTINUO 47(φ)x570(H)mm
RACING LEAD		LTA-505-3-R/Y/G-AC220V-WJ-FZL3	T. DE LUZ R/A/V+ZUMB. 220VAC INTERMITENTE 47(φ)x570(H)mm
RACING LEAD		LTA-505-3-R/Y/G-DC24V-WJ-FZL3	T. DE LUZ R/A/V+ZUMB. 24VDC INTERMITENTE 47(φ)x570(H)mm
RACING LEAD		TBL-832-R-AC220V-J	CIRCULINA ROJA 220VAC ZUMB. φ=86mm H=184mm
RACING LEAD		TBL-832-R-AC220V	CIRCULINA ROJA 220VAC φ=86mm H=184mm
RACING LEAD		TBL-832-R-DC24V-J	CIRCULINA ROJA 24VDC ZUMB. φ=86mm H=184mm
RACING LEAD		TBL-832-R-DC24V	CIRCULINA ROJA 24VDC φ=86mm H=184mm
SIKAIFU		ZJHP-16C-DN15-PN16-EN1092-PTFE-HEP	V. CONTROL DN15 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SIKAIFU		ZJHP-16C-DN20-PN16-EN1092-PTFE-HEP	V. CONTROL DN20 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SIKAIFU		ZJHP-16C-DN25-PN16-EN1092-PTFE-HEP	V. CONTROL DN25 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SIKAIFU		ZJHP-16C-DN40-PN16-EN1092-PTFE-HEP	V. CONTROL DN40 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SIKAIFU		ZJHP-16C-DN50-PN16-EN1092-PTFE-HEP	V. CONTROL DN50 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SIKAIFU		ZJHP-16C-DN65-PN16-EN1092-PTFE-HEP	V. CONTROL DN65 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092

SIKAIFU		ZJHP-16C-DN80-PN16-EN1092-PTFE-HEP	V. CONTROL DN80 PN16 0-150°C CUERPO WCB, ASIENTO SS304PTFE C/POS 4-20mA BRIDA EN1092
SLGPC		SL-2000-15	VALVULA ASIENTO INCLINADO SUS304 1/2" P. PILOTO 4-6BAR P MAX 16BAR TEMP. -10 - 180°C
SLGPC		SL-2000-25-63	VALVULA ASIENTO INCLINADO SUS304 1" P. PILOTO 4-6BAR P MAX 11BAR TEMP. -10 - 180°C
SLGPC		SL-2000-40-63	VALVULA ASIENTO INCLINADO SUS304 1 1/2" P. PILOTO 4-6BAR P MAX 12.5BAR TEMP. -10 - 180°C
SLGPC		SL-2000-50	VALVULA ASIENTO INCLINADO SUS304 2" P. PILOTO 4-6BAR P MAX 10BAR TEMP. -10 - 180°C
SLGPC		SL-2000-65	VALVULA ASIENTO INCLINADO SUS304 2 1/2" P. PILOTO 4-6BAR P MAX 10BAR TEMP. -10 - 180°C
SLGPC		SL-2000-80	VALVULA ASIENTO INCLINADO SUS304 3" P. PILOTO 4-6BAR P MAX 10BAR TEMP. -10 - 180°C
BELLOFRAM			961-070-000
SLGPC		2W-160-15-AC220V	VALVULA SOLENOIDE AIRE/AGUA 1/2" BRONCE SELLO NBR 220VAC 1-10 BAR -5 - 80°C
SLGPC		2W-160-15-AC24V	VALVULA SOLENOIDE AIRE/AGUA 1/2" BRONCE SELLO NBR 24VAC 1-10 BAR -5 - 80°C
SLGPC		2W-160-15-DC24V	VALVULA SOLENOIDE AIRE/AGUA 1/2" BRONCE SELLO NBR 24VDC 1-10 BAR -5 - 80°C
SLGPC		2W-250-25-AC220V	VALVULA SOLENOIDE AIRE/AGUA 1" BRONCE SELLO NBR 220VAC 1-10 BAR -5 - 80°C
SLGPC		2W-250-25-AC24V	VALVULA SOLENOIDE AIRE/AGUA 1" BRONCE SELLO NBR 24VAC 1-10 BAR -5 - 80°C
SLGPC		2W-250-25-DC24V	VALVULA SOLENOIDE AIRE/AGUA 1" BRONCE SELLO NBR 24VDC 1-10 BAR -5 - 80°C
SLGPC		2W-400-40-AC220V	VALVULA SOLENOIDE AIRE/AGUA 1 1/2" BRONCE SELLO NBR 220VAC 1-10 BAR -5 - 80°C
SLGPC		2W-400-40-AC24V	VALVULA SOLENOIDE AIRE/AGUA 1 1/2" BRONCE SELLO NBR 24VAC 1-10 BAR -5 - 80°C
SLGPC		2W-400-40-DC24V	VALVULA SOLENOIDE AIRE/AGUA 1 1/2" BRONCE SELLO NBR 24VDC 1-10 BAR -5 - 80°C
SLGPC		2W-500-50-AC220V	VALVULA SOLENOIDE AIRE/AGUA 2" BRONCE SELLO NBR 220VAC 1-10 BAR -5 - 80°C
SLGPC		2W-500-50-AC24V	VALVULA SOLENOIDE AIRE/AGUA 2" BRONCE SELLO NBR 24VAC 1-10 BAR -5 - 80°C

SLGPC		2W-500-50-DC24V	VALVULA SOLENOIDE AIRE/AGUA 2" BRONCE SELLO NBR 24VDC 1-10 BAR -5 - 80°C
SLGPC		2W-COIL-DIN-24VDC	SOLENOIDE + CONECTOR DIN PARA VALVULAS SERIE 2W 24VDC
SLGPC		2W-COIL-DIN-24VAC	SOLENOIDE + CONECTOR DIN PARA VALVULAS SERIE 2W 24VAC
SLGPC		2W-COIL-DIN-220VAC	SOLENOIDE + CONECTOR DIN PARA VALVULAS SERIE 2W 220VAC
SLGPC		2L-170-15-AC220V	VALVULA SOLENOIDE VAPOR 1/2" BRONCE SELLO PTFE 220VAC 1-15 BAR -5 - 180°C
SLGPC		2L-170-15-AC24V	VALVULA SOLENOIDE VAPOR 1/2" BRONCE SELLO PTFE 24VAC 1-15 BAR -5 - 180°C
SLGPC		2L-170-15-DC24V	VALVULA SOLENOIDE VAPOR 1/2" BRONCE SELLO PTFE 24VDC 1-15 BAR -5 - 180°C
SLGPC		2L-200-25-AC220V	VALVULA SOLENOIDE VAPOR 1" BRONCE SELLO PTFE 220VAC 1-15 BAR -5 - 180°C
SLGPC		2L-200-25-AC24V	VALVULA SOLENOIDE VAPOR 1" BRONCE SELLO PTFE 24VAC 1-15 BAR -5 - 180°C
SLGPC		2L-200-25-DC24V	VALVULA SOLENOIDE VAPOR 1" BRONCE SELLO PTFE 24VDC 1-15 BAR -5 - 180°C
SLGPC		2L-300-40-AC220V	VALVULA SOLENOIDE VAPOR 1 1/2" BRONCE SELLO PTFE 220VAC 1-15 BAR -5 - 180°C
SLGPC		2L-300-40-AC24V	VALVULA SOLENOIDE VAPOR 1 1/2" BRONCE SELLO PTFE 24VAC 1-15 BAR -5 - 180°C
SLGPC		2L-300-40-DC24V	VALVULA SOLENOIDE VAPOR 1 1/2" BRONCE SELLO PTFE 24VDC 1-15 BAR -5 - 180°C
SLGPC		2L-400-50-AC220V	VALVULA SOLENOIDE VAPOR 2" BRONCE SELLO PTFE 220VAC 1-15 BAR -5 - 180°C
SLGPC		2L-400-50-AC24V	VALVULA SOLENOIDE VAPOR 2" BRONCE SELLO PTFE 24VAC 1-15 BAR -5 - 180°C
SLGPC		2L-400-50-DC24V	VALVULA SOLENOIDE VAPOR 2" BRONCE SELLO PTFE 24VDC 1-15 BAR -5 - 180°C
SLGPC		2L-COIL-24VDC	SOLENOIDE PARA VALVULAS SERIE 2L 24VDC
SLGPC		2L-COIL-24VAC	SOLENOIDE PARA VALVULAS SERIE 2L 24VAC
SLGPC		2L-COIL-220VAC	SOLENOIDE PARA VALVULAS SERIE 2L 220VAC
SLGPC		3V2-10-06-AC220V-DIN-LED	EV 3/2 SIMPLE EFECTO NC G1/8" ø=14mm 220VAC
SLGPC		3V2-10-06-AC24V-DIN-LED	EV 3/2 SIMPLE EFECTO NC G1/8" ø=14mm 24VAC
SLGPC		3V2-10-06-DC24V-DIN-LED	EV 3/2 SIMPLE EFECTO NC G1/8" ø=14mm 24VDC
SLGPC		BSC-AC220V	BOBINA 220VAC VALVULAS SERIES 200/300/400
SLGPC		BSC-AC24V	BOBINA 24VAC VALVULAS SERIES 200/300/401

SLGPC		BSC-DC24V	BOBINA 24VDC VALVULAS SERIES 200/300/402
SLGPC		DIN-LED-AC	CONECTOR C/ LED 5-220VAC P/ BOBINA BSC
SLGPC		DIN-LED-DC	CONECTOR C/ LED 10-110VDC P/ BOBINA BSC
SLGPC		4V1-10-06-AC220V-DIN-LED	EV 5/2 SIMPLE EFECTO G1/8" ø=12mm 220VAC
SLGPC		4V1-10-06-AC24V-DIN-LED	EV 5/2 SIMPLE EFECTO G1/8" ø=12mm 24VAC
SLGPC		4V1-10-06-DC24V-DIN-LED	EV 5/2 SIMPLE EFECTO G1/8" ø=12mm 24VDC
SLGPC		4V1-30C-06-AC220V-DIN-LED	EV 5/3 DOBLE EFECTO CENTRO CERRADO G1/8" ø=9mm 220VAC
SLGPC		4V1-30C-06-AC24V-DIN-LED	EV 5/3 DOBLE EFECTO CENTRO CERRADO G1/8" ø=9mm 24VAC
SLGPC		4V1-30C-06-DC24V-DIN-LED	EV 5/3 DOBLE EFECTO CENTRO CERRADO G1/8" ø=9mm 24VDC
SLGPC		SSC-AC220V	BOBINA 220VAC VALVULAS SERIE 100
SLGPC		SSC-AC24V	BOBINA 24VAC VALVULAS SERIE 100
SLGPC		SSC-DC24V	BOBINA 24VDC VALVULAS SERIE 100
SLGPC		DINS-LED-AC	CONECTOR C/ LED 5-220VAC P/ BOBINA SSC
SLGPC		DINS-LED-DC	CONECTOR C/ LED 10-110VDC P/ BOBINA SSC
SLGPC		HLP-110	PRESOSTATO RANGO 1-10BAR DIFERENCIAL 1-30BAR
SLGPC		AT03-RS	SENSOR MAGNETICO 5-240VAC 5-110VDC 2 HILOS NA
SLGPC		4H230C-08	VALVULA PALANCA 5/3 CENTRO CERRADO G1/4", RETORNO POR RESORTE
SLGPC		4H230C-08-L	VALVULA PALANCA 5/3 CENTRO CERRADO G1/4", CON RETENCION
SLGPC		100M-5-F	MANIFOLD 5 VALVULAS SERIE 200
SLGPC		200M-5-F	MANIFOLD 5 VALVULAS SERIE 200
SLGPC		200M-5-F	MANIFOLD 5 VALVULAS SERIE 201
SLGPC		AC3010-02D	FRL 1/4" 1700L/min 0-10BAR REGUL. 0.5 - 8.5BAR DRENAJE AUTOMATICO
SLGPC		PC-0601	CONECTOR RAPIDO 1/8" x 6mm
SLGPC		PC-0602	CONECTOR RAPIDO 1/4" x 6mm
SLGPC		PMM-0600	RACOR PASAMURO 6mm

SLGPC		PUT-0600	CONECTOR "T" 6mm
SLGPC		SL-0601	REGULADOR DE FLUJO NEUMATICO 1/8" x 6mm